

66356
SOV/81-59-19-67722

The Spectral Analysis of Titanium, Molybdenum and Their Alloys for Nitrogen, Hydrogen and Oxygen

of N determination at the excitation of the spectrum by a low-voltage pulse discharge from a capacitance of $4,000 \mu$ farad has been shown. The determination of 0.1 - 1% O in Ti is carried out also in a pulse discharge but at a capacitance of 400μ farad without introduction of inductance; the discharge vessel is filled up with helium to a pressure of 500 mm Hg. The distance between the sample and the carbon rod of 6 mm in diameter sharpened to a truncated cone is 1 mm; the slit width of the spectrograph is 0.02 mm. The lines O 4705.32 and O 7771.9 Å are compared with the background of the spectrum. For photographing one spectrum 80 pulses are necessary. It has been shown that the intensity of the O lines depends in different ways on the energy of the discharge for different metals, e.g. for Ti the optimum intensity is reached at 400μ farad, for molybdenum at $4,500 \mu$ farad. Concentrations of 0.005 - 0.15% H in Ti are found at the excitation of spectra by a single low-voltage pulse discharge at a capacitance of $2,000 \mu$ farad, a tension of 270 v and a self-induction of 10μ henry between the sample cathode and the Cu-electrode of 3 - 5 mm in diameter sharpened to a point; the discharge takes place in the interelectrode gap of 0.3 mm in the air medium. The spectra are photographed on an ISP-51 spectrograph with a UF-85 camera

Card 2/3

SVENTITSKIY, N.S.; SUKHENKO, K.A.; FAL'KOVA, O.B.; GALONOV, P.P.;
TAGANOV, K.I.; ALPATOV, M.S.

Spectrum analysis of titanium, molybdenum, and their alloys
for nitrogen, hydrogen, and oxygen. *Fiz.sbor.* no.4:225-231
'58. (MIRA 12:5)

1. Vsesoyuznyy ordena Lenina nauchno-issledovatel'skiy institut
aviatsionnykh materialov.
(Gases in metals) (Spectrum analysis)

AUTHORS: Sul'chenko, K.A., Moiseyeva, K.A., Tishin, I.G., Metelina, L.D. 32-24-6-17/44

TITLE: The Analysis of Some Elements in Alloys With the Aid of the Photoelectric Stylometer (Analiz nekotorykh elementov v splavakh pri pomoshchi fotoelektricheskogo stilometra)

PERIODICAL: Zavodskaya Laboratoriya, 1958, Vol 24, Nr 6, pp 711-712 (USSR)

ABSTRACT: The determination of elements which had hitherto been insufficient when carried out by the photographic methods of spectral analysis, were carried out as e.g., the analysis of aluminum in nickel- and magnesium alloys with high Cu-, Zn- and Mg concentrations in aluminum alloys and a high tungsten content in steels. Experimental conditions are described, from which it may be seen that better results were obtained with a phase heating of 90° and a current of 3 amperes. Control of the stability of the position of the diagrams showed that considerable changes take place in spite of the fact that the temperature fluctuations were only slight. Results of considerable accuracy were obtained by means of carbon-, copper-, and nickel electrodes, in which case, however, calibration curves do not coincide. It was found that the quality of the experimental

Card 1/2

The Analysis of Some Elements in Alloys With the Aid
of the Photoelectric Stylometer

32-24-6-17/44

preparation and fixing of the sample exercise a considerable influence upon the accuracy of the results of the analysis. Determination of magnesium, zinc and copper in duraluminum B-95 and AMG and the determination of aluminum in a magnesium alloy showed, in addition to the results obtained by the aforementioned analyses, that the stylometer FES -1 can be used for the quantitative determination of elements in steels as well as in aluminum and nickel alloys. The error limits are given. Analysis, if the calibration curve is used, is said to take about 4 minutes. There are 2 figures and 1 table.

1. Alloys--Analysis 2. Spectrum analyzers--Performance

Card 2/2

The Analysis of Light and Refractory Alloys and Steels SCV/.8-23-9-25/57
for Photoelectrical Methods

shows the lines which were measured, as well as the concentration interval of the alloy elements, and the error in determination. Investigations were carried out of aluminum alloys with respect to magnesium, zinc, silicon, and copper, as well as of magnesium alloys to aluminum. The diagrams for the determination of silicon in the alloys Al-9, Al-5 and duralumin are shifted only little. The third part deals with the analysis of steels. These steels were investigated with regard to content of tungsten, chromium, manganese, and silicon, and table 3 gives the measured lines in Å, the width of the gap, the concentration intervals, and the errors in determination. It is found that, in the experiments carried out, no re-sharpening of the samples was necessary after the determination of an element, and that a considerable shortening of the time needed for the analyses was possible. The last part deals with the application of photoelectrical attachments in the spectrograph of the type ISP-22 for the analysis of aluminum- and magnesium alloys. Here, the emission within the range of wavelengths of 2900-2000 Å is recorded by means of a Geiger-Mueller counter. An arc generator of the type DG-1, the spark generator of the type

Card 2/3

SCV/48-23-9-29/57

24(7)
AUTHORS: Sukhenko, K. A., Grigoreva, V. S., Lindstrom, I. S., Sventits-
kaya, N. S., Galanov, P. P.

TITLE: The Determination of Oxygen in Technical Titanium by Means of
the Spectral Method

PERIODICAL: Izvestiya Akademii nauk SSSR. Seriya fizicheskaya, 1959,
Vol 23, Nr 9, pp 1116 - 1118 (USSR)

ABSTRACT: In the introduction mention is made of the papers published in
recent years on the determination of gases in metals in general,
and especially on the determination of oxygen in titanium.
(Refs 1-7). A pair of lines of oxygen and argon is given, by
means of which the concentration of oxygen in titanium was
determined within a range of 0.035 - 0.56%. Already in another
paper (Ref 7) it was shown that the influence of "third" ele-
ments is lacking, and it is possible by this method to deter-
mine the oxygen content with an accuracy equaling that of
vacuum melts or of bromine reductions. In the case of the ex-
periments carried out here, titanium standards with an oxygen
content of 0.01 - 2.0% were produced, in which case titanium-
sponge was mixed with TiO_2 in appropriate ratios. The electrodes

Card 1/3

The Determination of Oxygen in Technical Titanium
by Means of the Spectral Method

SOV/48-23-9-29/57

periments concerning the influence of annealing upon line intensities showed that the latter are independent of annealing. Experiments concerning the most favorable selection of the light source showed that low-voltage spark discharges are suited best. Figure 3 shows a diagram for the determination of oxygen in technical titanium according to the intensity of an oxygen line. This diagram was obtained by means of a low-voltage spark light source. Further investigations showed the usefulness of the DG-1-type generator for low-voltage spark discharges. There are 3 figures and 7 references, 2 of which are Soviet.

Card 3/3

The Determination of Nitrogen in Steels of Various Compositions

SOV/48-23-9-32/57

analytical methods. In the discharge chamber helium was used as a neutral medium. The diagram of figure 1 shows the calibration line for nitrogen determination in steel. A low-voltage spark generator and a pulsed-discharge generator were used as light sources. The scheme of a combined generator is shown by figure 2. In this circuit miniature electrolytic condensers and paper condensers are used, and semiconductors serve as rectifiers. In the spectral analysis of nitrogen in steels the influence of "third" elements was found. All experiments carried out on samples with about 1% Al yielded too high values. An increase in chromium with a simultaneous decrease in nickel causes a steeper slope of the calibration curve. There are 2 figures and 4 tables.

Card 2/2

The Setting of Standards for Various Alloys and the SOV/48-23-9-43/57
Investigation of the Influence of "Third" Elements Therein

ibration curves for the determination of boron and lead in various Ni-alloys. Experiments were then carried out by varying the amperage, the shape of the electrodes, and the like, in order to prevent the influence exercised by "third" elements, but these experiments were not successful. Finally, the possibility is pointed out of reducing the influence of "third" elements by a suitable selection of the light source. K. A. Moiseyeva took part in the investigation of titanium alloys. There are 1 figure, 1 table and 2 Soviet references.

Card 2/2

Sukhanko, K.A.

Gergichkori, N. N., Fornalova, V. M., Veselovskaya, I. M., Gusevina, V. P., Kosorobov, I. A., Demchenko, A. J., Galitskikh, Z. P., Podan, G. A., Mamot, T. A., Slobodcikova, K. N., Slobodcikov, K. A., Barabashov, T. V., Glazkov, G. O., Maikhanov, Sh. Kh.

卷之三

Zemel'skaya Laboratoriya, 1959, Vol. 25, No. 6, pp. 981-985 (ISSN 0041-1792).

- The authors determined the impurities of Si, Fe, Al, Mn, Mg, Cr, Cu, Ti, P, Sn, and Ba in thorium dioxide with a sensitivity of 10^{-2} to 10^{-3} % by burning a briquette from the sample mixed with carbon powder in the crater of a carbon electrode type furnace. The spectograph MZ-22 was used. The analytical double-photon device FZ-1 for the rapid analysis of open-throat furnaces, like for silicon dioxide ($15-30\%$), calcium oxide ($3-5\%$) and complete glass ($5-10\%$). There is a description of the operational method.³ The laboratory servoda (Plant laboratory) applies a spectrometer for the determination of titanium impurities (at approximately 0.05% concentration). It allows

84/1

All experiments to determine phosphorus impurities in steels were made at the plant "Metallurgist".⁴ The author reports on a method for localized spectroscopic analysis of steels and welded seams for the determination of phosphorus. The distribution of P was investigated in the case of austenitic and welding seams by the use of a DcI generator and a quartz spectrograph and the phosphorus contents of microscopic inclusions in the steel were determined.⁵ The author determines austenitic and ferritic micro-phosphorus in steels in which the sole sample (0.2 g) was treated with a saturated aqueous copper sulfate solution (2 ml) subsequently dried and melted in the crucible of two carbon electrodes. Spectrographs DcI and generator DcI-1 were used.⁶ The author developed a sensitive refractory substance by mixing the sample with carbon and barium nitrate (1:2) and separating it in the crater of a carbon electrode in an arc. A spectrograph DcI-2 was used. The use of this method was introduced at the plant "Metallurgist".⁷ Essentially simultaneously a method (Bimetallic Potentiometric) and Ziporobalistically served as a spectrometric method for the determination of phosphorus by a spectrometer (Zapreksa Plant of Refractory Materials).⁸ The author developed a sensitive refractory substance by mixing the sample with carbon and barium nitrate (1:2) and separating it in the crater of a carbon electrode in an arc.

potassium chloride. The determination takes only 2 hours. 70% of the sample mixed with carbon (1%) is put into the carbon dioxide and the specimen lines are measured with a spectrometer (NIR-20). The author, working in the laboratory of Institute of Laboratory (Institute of Laboratory) report the preparation of standard samples from technical Ti for the determination of hydrogen by the spectrum method. The article contains a description of the preparation method and the determination results according to different methods of the hydrogen in standard samples. The difference is maximum relative (15-25%). The author reports on a simple method for the determination of small quantities of H₂ and H₂O in calcium chloride water of high mineral contents. He used a spectrophotometer NIR-2 and standard samples. There are figures 1-10 and 1 table.

1) Laboratoriya nauchno-tekhnicheskogo sostavina (Laboratory of the Scientific Research Institute), 2) Zavod seryj solnitsev (Plant "Serp i Molot"), 4) Institut elektrosvarki im. G. A. Poltava i M. V. Neklyudova (Electric Welding Institute im. G. A. Poltava and M. V. Neklyudova), 5) Institute of Sciences of the USSR, 6) Stalnoprobadach metalloobrabotivayushchimi operatsiyami (Stalingradach Metallurgical Plant "Kazanets Otryazh"), 6) Vsesoyuznyj nauchno-issledovatel'skiy instytut spetsmaterialov (VNIISPM), 7) Vsesoyuznyj nauchno-issledovatel'skiy instytut spetsmaterialov (VNIISPM), 8) Tselinogradskij nauchno-issledovatel'skiy instytut spetsmaterialov (Tselinogradskij NII Spetsmaterialov), 9) Universitet nauchno-issledovatel'skiy, v. Tolyatti (Tolyatti Scientific Research Institute).

Introduction

APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9"

GALONOV, P.P.; SUKHENKO, K.A.; SVENTITSKIY, N.S.; ISAYEV, N.G.; TISHIN, I.G.;
BARASHEVA, T.V.

Determination of nitrogen in steel and of hydrogen in commercial
titanium and its alloys. Trudy kom.anal.khim. 10:190-195 '60.
(MIRA 13:8)

(Titanium--Analysis)
(Hydrogen--Analysis)
(Nitrogen--Analysis)
(Steel--Analysis)

MLADENTSEVA, O.I.; GOROZHANKINA, N.P.; SUKHENKO, K.A.; AKSENOVA, A.V.

Spectrum analysis of nickel alloys into basic components and impurities.
Trudy Kom. anal. khim. 12:355-365 '60. (MIRA 13:8)
(Nickel alloys--Analysis)
(Spectrum analysis)

SUKHOBAS, K.A., kand. tekhn. nauk, red.; KEMERITSKII, A.G., kand.
tekhn. nauk, reizhezhev; NOVOTREBN, S.I., red.; FUKHLIKOV, V.A.,
tekhn. red.

[Photoelectric methods of spectral analysis; collection of
articles] Fotoelektricheskie metody spektral'nogo analiza;
sbornik statei. Moskva, Gos. nauchno-tekh. izd-vo Oborongiz,
1961. 95 p. (MFA 15:1)

(Spectrum analysis)

S/081/62/000/016/007/043
B168/B186

AUTHORS: Sukhenko, K. A., Moiseyeva, K. A., Tishin, I. .., Bakanov,
D. G., Metelina, L. D., Al'tman, T. D.

TITLE: Photoelectric methods of analysis and their use in the
inspection of metals

PERIODICAL: Referativnyy zhurnal. Khimiya, no. 16, 1962, 119, abstract
16D106 (In collection: Fotoelektr. metody spektr. analiza.
M., Oborongiz, 1961, 5-19)

TEXT: Operational results of the Soviet quantometer АФС-10 (DFS-10) for
the analysis of alloys based on Al, Mg, Ni, Ti and Fe are given. A brief
description of the apparatus is followed by a list of the analytical lines
and concentration ranges and by a description of the analytical conditions
for various alloys; many calibration curves and tables are given showing
the reproducibility of determinations of the elements. The mean random
error in each case is calculated from 20-40 repeat determinations under
various conditions (light source, polarity, material of support electrode,
etc.). This method is shown to give greater analytical accuracy than the



Card 1/2

S/137/62/000/005/146/150
A052/A101

AUTHORS: Sukhenko, Z. A., Filatov, F. I., Galonov, P. P., Moiseyeva, K. A.,
Ketelina, L. D.

TITLE: An analysis of Al alloys on a multichannel quantometer

PERIODICAL: Referativnyy zhurnal, Metallurgiya, no. 5, 1962, 6, abstract 5X36
(V sb. "Fotoelektr. metody spektr. analiza", Moscow, Oborongiz,
1961, 44-66)

TEXT: A preliminary experience in analyzing AMg (AMg) and duralumin
alloys by means of a multichannel quantometer of APL company is reported. It is
recommended to use graphite and carbon electrodes dressed in the form of semi-
sphere and truncated cone, depending on the object of investigation. To increase
the accuracy of the analysis, the room where the quantometer is placed must
have an air conditioning installation securing temperature fluctuations of
 $\pm 0.5^{\circ}\text{C}$. For a quick analysis cast electrodes 6-8 mm in diameter are suitable as
samples, and also samples in the form of drawn wire and disks. The accuracy of
determination is 1-2%.

L. Vorob'yeva

[Abstracter's note: Complete translation]

Card 1/1

S/137/62/000/005/145/150
A052/A101

AUTHORS: Sukhenko, K. A., Al'tman, T. D.

TITLE: Investigation of Al alloy standards by photoelectric method

PERIODICAL: Referativnyy zhurnal, Metallurgiya, no. 5, 1962, 6, abstract 5K35
(V sb. "Fotoelektr. metody spektr. analiza". Moscow, Oborongiz,
1961, 70-81)

TEXT: An investigation and comparison of Soviet, English and German Al
alloy standards of various grades was carried out by photoelectric method on
DFO-10 (DFB-10) quantometer. A comparison of graduation diagrams for all
standards shows a fairly good concentration relationship for Cu, Zn, Fe, Cr,
Si, Ti, Mg and Mn. A certain discrepancy of graduation diagrams is due to the
different manufacturing technology of standards and to the different chemical
composition of alloys. The test samples of all alloys were prepared in the form
of rods 6-7 mm in diameter. This made it possible to obtain a finer structure
and a sufficient uniformity of chemical composition.

L. Verob'yeva

[Abstracter's note: Complete translation]

Card 1/1

S/137/62/000/005/148/150
A052/A101

AUTHORS: Sukhenko, K. A., Filatov, F. I., Moiseyeva, K. A., Galonov, P. P.
Metelina, L. D.

TITLE: Determination of boron in Ni alloys

PUBLISHER: Referativnyy zhurnal, Metallurgiya, no. 5, 1962, 6, abstract 5K40
(7 sub. "Fotonika", metody spektr. analiza". Moscow, Oborongiz,
1961, 82-86)

TEXT: To determine B, NCH + B (DOP-18) medium-dispersion quartz spectrograph and DFC-13 (DFP-13) spectrograph were used. In the same sample B was determined also by the photoelectric method on a multichannel quantummeter under low-voltage arc conditions. For a sample with 0.025% B the mean arithmetic error is $\pm 6\%$. The results obtained by photoelectric and photographic methods coincide well with the results of a chemical analysis.

L. Vorob'yeva

[Abstracter's note: Complete translation]

Card 1/1

*SEARCHED
SERIALIZED
FILED
AUG 11 1962*

105

PHASE I BOOK EXPLOITATION

SOV/6181

Ural'skoye soveshchaniye po spektroskopii. 3d, Sverdlovsk, 1960.
Materialy (Materials of the Third Ural Conference on Spectroscopy) Sverdlovsk, Metallurgizdat, 1962. 197 p. Errata slip inserted. 3000 copies printed.

Sponsoring Agencies: Institut fiziki metallov Akademii nauk SSSR. Komissiya po spektroskopii; and Ural'skiy dom tekhniki VSNTO.

Eds. (Title page): G. P. Skornyakov, A. B. Shayevich, and S. G. Bogomolov; Ed.: Gennadiy Pavlovich Skornyakov; Ed. of Publishing House: M. L. Kryzhova; Tech. Ed.: N. T. Mal'kova.

PURPOSE: The book, a collection of articles, is intended for staff members of spectral analysis laboratories in industry and scientific research organizations, as well as for students of related disciplines and for technologists utilizing analytical results.

COVERAGE: The collection presents theoretical and practical problems of the application of atomic and molecular spectral analysis in controlling the chemical composition of various materials in ferrous and nonferrous metallurgy, geology, chemical industry, and medicine. The authors express their thanks to O. V. Chentsova for help in preparing the materials for the press. References follow the individual articles.

Materials of the Third Ural Conference (Cont.)	SOV/6181
Kuranov, A. A., and N. P. Ruksha. Spectral determination of impurities in platinum	91
Sin'kov, N. A. Examination of some variants of calculating unknown impurity concentrations by the "additives" method	93
Fishman, I. S., and F. K. Sattarova. Chemical-spectral determination of carbides and intermetallic compounds in nickel alloys	99
Sukhenko, K. A., V. S. Grigor'yeva, I. S. Lindstrom, N. S. Sventitskiy, and P. P. Galonov. Methodology for spectral determination of oxygen in titanium and its alloys	101
Popov, B. V. Use of spectral analysis at the Ural Auto- motive Plant	102
Shlepkova, Z. I. Determination of phosphorus in copper alloys with the CT-7 stylometer	104

Card 8/15

S/046/62/026/007/016/030
B104/B138

AUTHORS: Buyanov, N. V., Komarovskiy, A. G., and Sukhenko, K. A.

TITLE: Photoelectric methods of spectrum analysis and their
industrial application

PERIODICAL: Akademiya nauk SSSR. Izvestiya. Seriya fizicheskaya,
v. 26, no. 7, 1962, 902-906

TEXT: Spectral analysis in Soviet industry is carried out with
photoelectric devices produced by the American firm ARL, the Italian firm
Optico-Milano, and the British firm Hilger, and also with the Soviet
quantometers $\Delta\Phi(-10)$ (DFS-10), $\Phi\Theta C-1$ (FES-1). Series production of the
10-channel $\Phi\Theta C-31$ (DFS-31) is planned to start in 1962. The DFS-10
is compared with the ARL quantometer, and found to be less accurate.
The following must be improved in the Soviet make: the amplifying and
recording system, light source, and the stand; some of the photocells
must be replaced by photomultipliers. In addition, the voltage and
frequency must be stabilized. There are 1 figure and 4 tables.

Card 1/1

S/048/62/026/007/020/030
B125/B104

AUTHORS:

Grigorova, V. S., Lindstrem, I. S., Sventitskiy, N. S.,
and Sukhenko, K. A.

TITLE:

Oxygen determination in low-melting metals and
alloys by the spectral method

PERIODICAL:

Akademiya nauk SSSR. Izvestiya. Seriya fizicheskaya,
v. 26, no. 7, 1962, 924-926

TEXT: The oxygen content in niobium and molybdenum alloys is best determined from their spectra with simultaneous extraction of the gases. The specimen was used as an anode of the discharge current circuit (24,000 μ F) of a low-voltage pulse generator. The experimental conditions can thus be easily standardized; the effect of impurities can be eliminated, and electrode erosion can be intensified. A niobium cone with 0.004% oxygen was used as a cathode. Aluminum cathodes can also be used. The discharge took place in commercial helium of 250 mm Hg. The oxygen content of He should be 0.01% at most; its nitrogen content should be sufficient for localizing the discharge. The spectra were

Card 1/2

KRIVOV, V.I.; TUFENKOV, N.I.; ASPRAKIMANOV, G.S.; SITNIKOV, G.V.

Formation intensive irradiation-less zones using a hydraulic
mechanical planer. Birobel no. 511-12 '64.

"Novosibirskiy neftyanoy nauchno-issledovatel'skiy institut, g.
Bugul'ma i trest "Allmet'yevburneft". (MIRA 18:5)

ABDRAKHMANOV, G.S.; KOMILOV, V.I.; SUKHENKO, N.I.

Hydraulic expander for increasing the diameter of a well.
Burenie no.4:3~5 '64.

(MIRA 18:5)

1. Tatarskiy neftyanoy nauchno-issledovatel'skiy institut, g.
Bugul'ma.

KRYLOV, V.I.; ABDRAKHMANOV, G.S.; SUKHENKO, N.I.

Use of drillable packers to exclude circulation-loss zones and
cave-ins. Burenie no.7:8-10 '64.

(MIRA 18:5)

1. Tatarskiy neftyanoy nauchno-issledovatel'skiy institut, g.
Bugul'ma.

PUSHEV, M.S., inzhener; SUMHENKO, S.D., inzhener.

Die-stamped compressed wood fiber furniture elements. Der.prem.
4 no.11:12-13 N '55. (MLRA 9:2)
(Wood, Compressed)

"APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9

APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9"

68-9-1/15

AUTHORS: Sukhenko, S. I.

TITLE: Preparation of a Charge of Kuznetsk Coal by Selective Crushing (Podgotovka shikhty iz kuznetskikh ugley metodom izbiratel'nogo drobleniya)

PERIODICAL: Koks i Khimiya, 1957, Nr 9, pp. 3-7 (USSR)

ABSTRACT: Advantages of applying preferential grinding for coking blends from Kuznetsk coals were investigated. The size distribution of coals as received is given in Table 1, and the petrographic composition of the above coals in Table 2. Under works' conditions of crushing, the fusite group is concentrated in a size range exceeding 2-3 mm. Data on the thickness of the plastic layer and ash content of large and small size fractions of coals before crushing are given in Table 3. As the first step, the strength of coke produced from the individual size ranges of works crushing was studied. The best coke was obtained from size ranges 2-0 mm and 1-0 mm. An experimental blend was made from coals as received (except that coal above 50 mm was precrushed to -50 mm) and divided into three parts. One part was crushed by the usual works' practice, the second part was crushed as follows: screened at 3 mm, +3 mm crushed to pass 3 mm and well mixed together. The third part: screened at 2 mm, above 2 mm crushed to pass 10 mm and again -2 mm fraction removed. The

Card 1/3

68-12-3/25

AUTHORS: Ammosov, I.I., Doctor of Geological and Mineralogical Sciences
Yeremin, I.V., Candidate of Technical Sciences,
Sukhenko, S.I., Candidate of Technical Sciences and
Oshurkova, L.S.

TITLE: Calculation of Blends for Coking on the Basis of the Petrographic Features of Coals (Raschet shikht dlya koksovaniya na osnove petrograficheskikh osobennostey uglev)

PERIODICAL: Koks i Khimiya, 1957, No.12, pp. 9-12 (USSR)
ABSTRACT: A method of blending coals for coking based on petrographic analysis is proposed. The method is based on principles developed in earlier work (Ref.1). On the basis of rank and petrographic composition, some new characteristics of coals were established, namely: leaning index and coking coefficient. The leaning index is the ratio between the amount of leaning components present in a blend to the amount of leaning components necessary for a given blend to obtain optimum ratio between cokable and inert components in the blend. Vitrite, leiptinite and 1/3 of semi-vitrite are included as cokable components and fusite group and 2/3 of semi-vitrite as inert components. The sum of cokable and inert components equals 100% of the organic part of coal ($\Sigma C + \Sigma I = 100\%$); the division of coals according to rank (position in metamorphic

Card 1/4

68-12-3/25

Calculation of Blends for Coking on the Basis of the Petrographic Features of Coals.

$$K = \frac{\sum c_1 \cdot K_1 + \sum c_2 \cdot K_2 + \dots + \sum c_n \cdot K_n}{\sum_{l=1}^n c_l}$$

where K_1, K_2, \dots, K_n - coking coefficient of corresponding ranks at a given content of leaning components in the blend. Values for K are given in fig.2. From the leaning index and coking coefficient determined for a given blend, the corresponding coke strength can be determined from the diagram (Fig.3). An example of such calculations is given. It is stated that a very good agreement between the calculated and determined values for coke strength was obtained (correlation coefficient determined for 44 cases was 0.827). It is pointed out that maximum fissuring of coke is obtained when the individual components of a coal blend differ considerably in their rank. It is concluded that the method proposed can be used for calculating the required composition of multi-component blends containing fusenic coals and up to 25% of

Card 3/4

"APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9

AMMOSOV, I.I.; SUKHENKO, S.I.; YEREMIN, I.V.; OSHURKOVA, L.S.

Calculating coke charges on the basis of the petrographic
characteristics of coals. Trudy IGI 8:21-30 '59.

(MIRA 13:1)

(Coke industry) (Coal)

APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9"

KUPERMAN, P.I.; SUKHENKO, S.I., kand.tekhn.nauk

New data on the vertical shrinkage of the charge from Kuznetsk coals.
Koks i khim. no.4:20-24 '60. (MIRA 13:6)

1. Vostochnyy uglekhimicheskiy institut (for Kuperman). 2. Kuznetskiy
metallurgicheskiy kombinat (for Sukhenko)
(Coal--Carbonisation)

FRISHBERG, V.D.; SUKHENKO, S.I.

Coking time for coal charges containing an increased amount of gas
coal from the Kuznetsk Basin. Koks i khim. no.8:11-12 '60.

(MIRA 13:8)

1. Vostochnyy uglekhimicheskiy institut (for Frishberg). 2. Kuznetskiy
metallurgicheskiy kombinat im. I.V.Stalina (for Sukhenko).
(Coal--Carbonization)

ZHEREBIN, B.N.; MISHIN, P.P.; KUDOYAROV, M.S.; SUKHENKO, S.I.; RASKIN, V.Z.;
OSTROUKHOV, M.Ya.; RAKOV, V.V.

Experimental blast furnace smelting using coke from large-capacity
coke ovens. Koks i khim. no.2:23-29 '64. (MIRA 17/4)

1. Kuznetskiy metallurgicheskiy kombinat (for Raskin).
2. Chelyabinskiy institut stali (for Ostroukhov). 3. Kuznetskiy
filial Vostochnogo uglekhimicheskogo instituta (for Rakov).

9(2)

SOV/107-59-4-39/45

AUTHOR: Arytyunova, I., Sukhenko, T. (Baku)

TITLE: AC Voltage Stabilization by One Gas-Discharge Stabilizer Tube (Stabilizatsiya peremennogo napryazheniya odnim gazorazryadnym stabilitronom)

PERIODICAL: Radio, 1959, Nr 4, p 56 (USSR)

ABSTRACT: AC voltage stabilization circuits usually are composed of two gas-discharge tubes as shown in Figure 1. The authors found that the application of one SG-2P gas-discharge tube will provide an equal stabilization effect. Figure 2 shows a voltage stabilization circuit with one gas-discharge tube. The authors have the opinion that the latter circuit will be adequate in a number of possible applications. There are 2 circuit diagrams and 1 graph.

Card 1/1

1952, V.

Steel Industry, and Trade

Collective agreement of a metallurgical plant, V pom. profaktivu, 13, No. 6, 1952

Monthly List of Russian Accessions, Library of Congress, May 1952, Unclassified.

NUL'MAN, N. (Kiyev); SUKHENKO, V., glvnnyy inzhener (Kiyev).

Obtaining decorative-finishing laminated plastics. Stroi.mat.,
izdel.i konstr. 2 no.6:15-16 Je '56. (MLRA 9:8)

1. Direktor kombinata "Stroydetal'" (for Nul'man).
(Plastics) (Tiles)

SUKHENKO, V.F.

DOLGOV, S.I., doktor sel'skokhozyaystvennykh nauk; SUKHENKO, V.F., ag-
ronom.

Effectiveness of productive leaching of saline soils of the Mili
Steppe in the Kura-Aras Lowlands. Gidr. i mel. 6 no.8:51-62 Ag '54.
(MILRA 7:9)

(Mili Steppe--Soil conservation) (Soil conservation--Mili Steppe)

PRODANOV, V.I., starshiy nauchnyy sotrudnik; MARCHENKO, N.S., veterinarnyy
vrach; SUKHENKO, V.P., veterinarnyy fel'dsher

Treatment of mastitis in cows. Veterinariia 39 no.1:43-45 Ja
'63. (MIRA 16:6)

1. Krasnodarskaya nauchno-issledovatel'skaya veterinarnaya stantsiya
(for Prodanov). 2. Krasnodarskaya krayevaya veterinarno-
bakteriologicheskaya laboratoriya (for Marchenko). 3. Kolkhoz imeni
Kalinina, Novotitarovskogo rayona, Krasnodarskogo kraja (for
Sukhenko).

(Udder--Diseases)

SUKHENKO, YE. K.

VOLODARS'KA, D.M.; GOROKHOVS'KYY, M.E.; KONDRAT'YEV, S.F.; PRAKHOV, M.M.; KOVPANEKO, T.M.; SUKHENKO, Ye.K.; LYASHEVS'KA, V.F.; ZHEL'NIO, T.M.; KHIVRICH, G.K.; GEORGIYEVSKYY, M.I.; NAYVEL'T, E.M.; DENISENKO, L., veduchiy redaktor; PATSALYUK, P., tekhnichniy redaktor

[Hints for everyday living] Pobutovi porady; Vydr. 3-ia, vypr. i dop. Kyiv, Derzh. vyd-vo tekhn.lit-ry URSR, 1957. 184 p.
(Home economics) (MIRA 10:8)

GERMAN, A.N., veterinarnyy vrach; ZOZULYA, Ye.A., veterinarnyy vrach;
SUKHENKOV, G.Ye.

Sanguinicolosis of carp. Veterinariia 41 no.8:54-55 Ag '64.
(MIRA 18:4)

1. Respublikanskaya veterinarnaya laboratoriya Ukrainskoy SSR
(for German, Zozulya). 2. Ukrainskiy nauchno-issledovatel'skiy
institut rybnogo khozyaystva (for Sukhenkov).

SUKHERMAN, B.

The KShP-3 bailer-screw grain loader is a good machine. Muk.-elev.
prom. 28 no.2:30 F '62. (MIRA 15:3)

1. Direktor Mogilev-Podol'skoy realizatsionnoy bazy.
(Grain-handling machinery)

SUKHOTAYA, I.P. (Kiyev, ul. Artema, 74, av.10)

Development of reticular matter of the spinal cord in man [with
summary in English]. Arkh.smat.gist. i embr. 34 no.3:30-36 Ky-Je '57.
(MIRA 10:10)

1. Iz kafedry normal'noy anatomi (zav. - zasluzhennyy deyatel' nauki
prof. M.S.Spirov) Kiyevskogo ordena Trudovogo Krasnogo Znameni medi-
tsinskogo instituta im. akad. A.A.Bogomol'tsa.

(SPInat SSSR, embryol.
reticular matter develop.in man (Eng))

SUKHETSKAYA, M. P.

SUKHETSKAYA, M. P.- "Reticulate Matter in the Human Spinal Cord." Kiev Order of Labor Red Banner Med Inst imeni Academician A. A.Bogomolets, Kiev, 1955 (Dissertations for Degree of Candidate of Medical Sciences)

SO: Knizhnaya Letopis' No. 26, June 1955, Moscow

SHEVELEV, F.A., doktor tekhn.nauk; GORIN, G.S., inzh.; MINTS, D.M., prof., doktor tekhn.nauk; SUKHIASHVILI, N.K., kand.tekhn.nauk; MIKHAYLOV, N.M., inzh.; NINEMYAGI, D.K., red.izd-va; TEMKINA, Ye.L., tekhn. red.

[Fourth International Water Supply Congress] IV Mezhdunerosodnyi kongress po vodosnabzheniu. Pod red. F.A. Sheveleva. Moskva, Gos. izd-vo lit-ry po stroit., arkhit. i stroit. materialam, 1960. 111 p. (MIRA 13:9)

1. International Water Supply Congress. 4th, Brussels, 1958.
2. Deystvitel'nyy chlen Akademii stroitel'stva i arkhitektury SSSR (for Shevelev).
(Water-supply engineering--Congresses)

SUKHIASHVILI, N.K.

One more important potential. MTO 3 no.4:7 Ap '61. (MIRA 14:3)

1. Zamestit' ministra mestnogo khozyaystva Gruzinskoy SSR.
(Compost) (Sewage as fertilizer)

SUKHIAASHVILI, N.¹_A, kand.tekhn.nauk

Valuable garbage. MTO 3 no.12:22 L '61.

(MIRA 15:1)

1. Zamestitel' ministra mestnogo khozyaystva Gruzinskoy SSR.
(Refuse and refuse disposal)

SUKHIKH, A.A.; KRATIROV, D.A.

Treating bundles of export lumber with antiseptics. Der. prom.
14 no. 5; 20-21 My '65. (MIRA 18;6)

1. Arkhangel'skiy lesopil'no-derevoobrabatyvayushchiy kombinat
imeni V.I. Lenina.

OSKIN, L.N.

Development of cutaneous lymphangioma in a dog
extremis in a dog during the execution of radical operation.
Trudy tshev.gos.med.inst. 21:2-16 '64.

(VILK 1961)

1. Katedra normal'noy i patologicheskoy anatomii
(zav. - prof. V.Y. Golev) i katedra normal'noy anatomii lige
Leningrad'skogo meditsinskogo instituta imeni skadriki s. S. Devlova
(zav. - prof. M.G. Petrusov).

BABCHENKO, V.N., otv.red.; SUKHIKH, L.G., starshiy inzh.-agrometeorolog,
red.; MARTYNOV, S.I., red.; PERMYAKOVA, A.I., red.; ROGOVSKAYA,
Ye.G., red.; SERGEYEV, A.N., tekhn.red.

[Agroclimatic handbook for Perm Province] Agroklimaticheskii
spravochnik po Permskoi oblasti. Leningrad, Gidrometeor.izd-vo,
1959. 131 p.
(MIRA 13:11)

1. Russia (1923- U.S.S.R.) Glavnoye upravleniye gidrometeorolo-
gicheskoy sluzhby. Ural'skoye upravleniye. 2. Nachal'nik Ural'skogo
upravleniya gidrometsluzhby (for Babchenko). 3. Direktor Sverdlovskoy
gidrometeorologicheskoy observatorii (for Martynov). Nachal'nik otde-
la klimata Sverdlovskoy gidrometeorologicheskoy observatorii (for
Permyakova).

(Perm Province--Crops and climate)

BABCHENKO, V.N., otv.red.; ZHDANOVA, L.P., red.; NEDOSHIVINA, T.G., red.
Prinimali uchastiey: MARTYNOV, S.I., red.; PERMYAKOVA, A.I.,
red. SUKHIKH, L.G. red.; BRAYNIKA, M.I., tekhn.red.

[Agroclimatic manual for Chelyabinsk Province] Agroklimaticheskii
spravochnik po Cheliabinskoi oblasti. Leningrad, Gidrometeor.
izd-vo, 1960. 155 p.

(MIRA 14:4)

1. Russia (1923- U.S.S.R.) Glavnoye upravleniye gidrometeorolo-
gicheskoy sluzhby. Ural'skoye upravleniye. 2. Direktor
Sverdlovskoy gidrometobservatorii (for Martynov). 3. Nachal'nik
otdela klimatologii Sverdlovskoy gidrometobservatorii (for
Permyakova).

(Chelyabinsk Province--Crops and climate)

SUKHIKH, L.I. (Moskva)

Determining the optimum shape of a longitudinal groove for
rotating shafts. Izv. AN SSSR Otd. tekhn. nauk. Mekh. i
mashinostr. no.2:177-179 Mr-Ap '63. (MIRA 16:6)

(Shafting)

PHASE I BOOK EXPLOITATION

sov/4086

Beda, L. M., L. N. Korolev, N. V. Sukhikh, and T. S. Frolova

Programma avtomaticheskogo differentsirovaniya dlya mashiny BESM (Automatic
Differentiation Program for the BESM [High-Speed Electronic Computer])
Moscow, 1959. 19 p. (Series: Elektronnyye vychislitel'nyye mashiny)
500 copies printed.

Sponsoring Agency: Akademiya nauk SSSR. Institut tochnoy mekhaniki i
vychislitel'noy tekhniki.

PURPOSE: This booklet is intended for programmers and engineers working
in the field of computer technology.

COVERAGE: The booklet contains a general description of a program and
method for the analytical differentiation of functions on the Soviet
high-speed digital computer BESM. The method and program were worked
out at the Institute of Precise Mechanics and Computer Technology,
Academy of Sciences USSR. At the end of the book are found block-
diagrams for BESM solution of the following mathematical problems: the
representation of a mathematical expression by a sequence of pairs; the
derivation of the derivatives of elementary pairs; and the synthesis of
Card 1/2

KRIKUN, V.Ya., inzh.; SUKHIKH, S.P., inzh.

Bringing pipe bending to the assembly site. Stroi. truboprov. 8
no.3:29-30 Mr '63. (MIRA 16:5)
(Pipe bending--Equipment and supplies)

SUKHIKH, S.P.

Movable machine for cold pipe bending. Biul.tekh.-ekon.inform.Gos.-
nauch.-issl.inst.nauch.i tekhn.inform. 16 no.7:14-15 '63.
(MIRA 16:8)

(Pipe bending)

S/190/63/005/004/020/020
B101/B220

AUTHORS: Ivanov, V. S., Sukhikh, T. A., Breger, A. Kh., Osipov, V. B.,
Gol'din, V. A.

TITLE: Radiation polymerization of maleic N-phenyl maleimide in
solid state

PERIODICAL: Vysokomolekulyarnyye soyedineniya, v. 5, no. 4, 1963, 628

TEXT: Maleic' N-phenylinide, m.p. 89 - 90°C, was polymerized by Co⁶⁰ gamma irradiation. The irradiation yield was ~1000 molecules per 100 ev. At 87.5°C, 0.65 Mr/hr and a dose of 2.2 Mr, 32.5 % of polymer was obtained. At 20°C this yield decreased to 4.5 - 6.5 %. More complete polymerization (79.5 %) was achieved by further heating to 100°C of the ampoules that had been irradiated at 82°C. With 2 - 5 Mr light yellow crystalline powders were obtained, with 10 Mr brown amorphous substances. Dependent on the conditions of production, the polymers are heat-resistant up to 250 - 330°C, soluble in dimethyl formamide and CS₂, insoluble in H₂O, acetone, CCl₄, benzene, toluene, heptane and cyclohexane. The IR spectra of the polymers showed bands of the phenyl ring, the carbonyl group and the C-N bond.

Card 1/2

S/190/63/005/004/020/020
B101/B220

Radiation polymerization of ...

From a comparison of the IR spectra of monomer and polymer it was concluded that in the course of polymerization the C-C bonds are opened.

SUBMITTED: July 26, 1962

Card 2/2

S/0190/64/006/005/0782/0786

ACCESSION NR: AP4037271

AUTHORS: Ivanov, V. S.; Sukhikh, T. A.; Medvedev, Yu. V.; Breger, A. Kh.; Osipov, V. B.; Gol'din, V. A.

TITLE: Studies in radiation polymerization. 3. Radiation polymerization of piperylene in channel complexes of urea

SOURCE: Vy'sokomolekulyarnye soyedineniya, v. 6, no. 5, 1964, 782-786

TOPIC TAGS: piperylene polymerization, urea clathrate complex, endocytic clathrate component, channel polymerization, tube structure, trans piperylene polymer

ABSTRACT: Urea clathrate complexes with piperylene as endocytic component were prepared by mixing 1 gm urea with 0.001—0.1 ml methanol, cooling in a glass ampule to -78°C, and adding 1-3.7 moles of cooled piperylene per mole of urea. The polymerization of piperylene was achieved by γ -irradiation with Co60. Parallel studies on block-polymerization of piperylene were conducted at -78°C with irradiation doses of 30 Mrad. After 2 to 6 weeks at -78 to -45°C, the residual piperylene monomer was removed by means of a vacuum pump. The urea was then dissolved in 10% acetone, leaving polymers whose specific viscosity, degree of unsaturation, and

Card 1/2

SOURCE CODE: UR/0000/66/000/000/0019/0026

ACC NR: AT7000960

ACC NR: AT7000960 SOURCE: 301
AUTHOR: Pavlovich, N. V. (Doctor of technical sciences; Deceased); Sukhikh, V. T.
1. Kiev Institute of Light Industry (Kiyevskiy tekhnologicheskiy

ORG: Kiev Technological Institute of Light Industry
institut legkoy promyshlennosti)

TITLE: Thermophysical properties of ϵ -caprolactam and poly- ϵ -caprolactam
SOURCE: AN UkrSSR. Teplofizicheskiye svoystva veshchestv (Thermophysical properties of materials). Kiev, Izd-vo Naukova dumka, 1966, 19-26

SUB CODE: 07.20 /

SUBM DATE: 10Mar65/

ORIG REF: 005

Card 1/1

SUKHIKH, V. T. and PAVLOVICH, N. V. (Kiev technological institute of light industry)
SUKHIKH, V. T. and PAVLOVICH, N. V. "Data on investigations of thermal physical properties of certain monomers."

"Data on investigations of thermal physical properties of certain monomers."
Report presented at the Section on Thermal-physical Properties and Non-stationary
Thermal Capacity, Scientific Session, Council of Acad. Sci. Ukr SSR on High Temperature
Physics, Kiev, 24 Apr 1963.

Reported in Teplofizika Vysokikh temperatur, No. 2, Sep-Oct 1963, p. 321, JPRS 24,651.
19 May 1964.

SUKHIN, D. Ye.

SUKHIN, D. Ye. -- "The Development and Investigation of a New Screw Mechanism for the Working Part of Plucking Equipment." Joint Academic Council, All-Union Sci Res Inst of the Mechanization of Agriculture (VIM), and All-Union Sci Res Inst of the Electrification of Agriculture (VIERKh). Moscow, 1955. (Dissertation for the Degree of Candidate in Technical Sciences)

cc: Knizhnaya Letopis', No 1, 1956

SUKHIN, G.M.

Effect of transplantation of the bone marrow in treating
sarcoma M-1 in rats with high doses of Thic-TEPA. Vop.
onk. 11 no.3:42-52 '65. (MIRA 18:6)

1. Iz laboratorii eksperimental'noy terapii opukholey (zav. -
doktor med. nauk V.M. Bergol'ts) Gosudarstvennogo onkologicheskogo
instituta imeni P.A. Gertseva (dir. - prof. A.N. Novikov).

13089

SUKHIN, K.

USSR/Cities - Leningrad 6202.0318
Manufacturing Areas 4401.0200

Dec 1947

"Industrial Leningrad," K. Sukhin, 5 pp

"Slavyane" No 12

Short discussion of some of more important industrial installations of city and indication of items produced in some cases. Plants mentioned are: Elektrosila imeni Kirov, Krasnyy Treugol'nik, Ravenstvo, Krasnyy Vyborzhets, plants imeni Stalin, imeni Kotlyakov, imeni Sverdlov, Krasnaya Vagranksa, Metal-list, Vulkan, Skorokhod, Bol'shevik and Rabochiy. More detailed information is given concerning Elektrosila imeni Kirov and turbine plant imeni Stalin.

13089

LC

124-57-2-2496

Translation from: Referativnyy zhurnal, Mekhanika, 1957, Nr 2, p 138 (USSR)

AUTHORS: Kunin, N. F., Sukhin, L. T.

TITLE: The Plastic Compression of Metals at Various Temperature Levels (Plasticheskoye szhatiye metallov pri razlichnykh temperaturakh)

PERIODICAL: Tr. Chelyabinskogo in-ta mekhaniz. i elektrifik. s. kh., 1955,
Nr 5, pp 134-142

ABSTRACT: Presentation of the results of experimental investigations on the plastic compression of a number of metals at various temperature levels; the purpose of the work was the confirmation that for that type of deformation the stresses are an exponential function of the temperature over a broad interval of temperatures. The investigation comprised copper, silver, aluminum, zinc, lead, tin, lithium, sodium, and cadmium. The paper is preceded by a brief survey of the literature on the subject.

1. Metals--Stressed 2. Metals--
temperature factors G. A. Smirnov-Alyayev

Card 1/1

31807

Thermoelectric Phenomena in Deformation of Metals

S/137/60/000/04/11/015

Deforming installation. One of the joints was placed in melting ice, the other in oil. The magnitude of thermo-emf was measured using a mirror galvanometer. It was shown that the thermo-emf produced by deformation consisted of an elastic and a residual component. The elastic thermo-emf produced, may be determined as the difference of thermo-emf under load and after unloading. The elastic component of the thermo-emf produced increased with higher stress. The stress under which the difference between elastic and non-elastic components arises, is designated as the thermoelectric yield limit. It was established that the thermoelectric yield limit of the investigated metals approached the mechanical yield point. During expansion, the elastic thermo-emf has a sign that is opposite to the residual thermo-emf; this causes an inversion of the sign of full thermo-emf if the stress is sufficiently high. It was shown that for the thermo-emf produced, elastic-residual phenomena were observed in the form of a thermoelectric hysteresis.

L. G.

✓

Card 2/2

SUKHIN, L.T. (Chelyabinsk)

Modification of a Chinese toy. Politekh.obuch. no.10:48-50
0 '59. (MIRA 13:2)
(Scientific recreations)

SUKHIN, N.L.

Make better use of the transformers. Put' i put.khoz. 7 no.12:16
'63. (MIRA 16:12)

1. Nachal'nik distantsii, Lozovaya, Yuzhnay dorogi.

USSR / Cultivated Plants. Plants for Technical Use. M
Oil Plants. Sugar Plants.

Abs Jour : Ref Zhur - Biologiya, No 6, 1959, No. 25014

period, sowing was conducted with the application of mulch. The best species of mulch, under conditions of the Issyk-Kul'skaya Oblast' is humus. Results of determining the amounts of weight gain and the diameter of the root collars indicate that the optimal sowing periods of the mulberry seeds in this oblast' must be considered to be the first half of May. -- O. P. Plyusnina

Card 2/2

SUKHIN, V.S.

Cancer of the stomach; data from the surgical clinic of the
Blagoveshchensk Medical Institute and of the Amur Province
Oncological Clinic. Vop. onk. 7 no.1:94-96 '61. (MIRA 14:2)
(STOMACH--CANCER)

SUKHIN, V.S.

Case of bilateral distal epiphysiolytic of the femur. Ortop.
(MIRA 14:5)
travm.i protez. 22 no.1:74-75 Ja '61.

1. Iz kliniki obshchey khirurgii (ispolnyayushchiy obyazannosti
zaveduyushchego - dotsent A.G.Gladchenko) Blagoveshchenskogo
meditsinskogo instituta. Adres avtora: Blagoveshchensk-na-Amure,
Pochtamtskiy pereulok, d.1., Klinika obshchey khirurgii.
(FEMUR--WOUNDS AND INJURIES)

VOLKOV, Ivan Georgiyevich; GLIKIN, Boris Abramovich; ZABOLOTNYY, Il'ya
Yevtikhiyevich; LIKHOTINSKIY, Valentin Sergeyevich; SPEKTOR,
David Borisovich; YAVORSKIY, Anatoliy Georgiyevich; SUKHIN, Ye.T.,
red.; MARTIROSOV, A.Ye., red.; VAYL', T.I., red.izd-va; LAVRENOVA,
N.B., tekhn.red.

[Reference book for sea harbor mechanizers] Spravochnik mekhanizatora morskogo porta. Moskva, Izd-vo "Morskoi transport," 1959.
(MIRA 13:2)

462 p.

(Harbors--Equipment and supplies)
(Cargo handling--Equipment and supplies)

Conditions of formation and stability of bitumen emulsions. E. S. Medvedkov and A. F. Sukhina. *Vysok. Molek. Soedin.* 1, 105-24 (1967). A study was made of the strength of the adsorbed layer of the emulsifying agent on bitumen, also, of the surface tension of bitumen in contact with the emulsifier, of the degree of dispersion of bitumen and of the stability of the emulsion. Use of bitumen

men at a high temp. lowers the quality of the emulsion owing to interaction between the bitumen and the soap emulsifier. The effect of NaOH, NaCl, KCl, CaCl₂, CuSO₄, MgSO₄, BeCl₂ and BaCl₂ on bitumen emulsions was investigated. Univalent ions, when used up to a certain max., improve bitumen-H₂O-soap emulsions, while the other ions cause their partial or complete destruction. Bitumen emulsions are more stable at low temps. than at high, owing to decrease in strength of the adsorbed layer of the emulsifier on the bitumen at higher temps. S. J. Madorsky

Control of condensation of neoleucorite resins. F. S. Malyukov and A. L. Sukharev. *Og. Chem. Ind. U.S.* 2, 40 - 6, '61 (Ref.). The process of condensation of $\text{CH}_2=\text{CH}-\text{CH}_2-\text{CH}_2-\text{CH}_2=\text{CH}_2$ with MgCl_2 is most conveniently followed from relative measurements. The temp. coeff. of the reaction is 0.1 at 00-70°. The velocity rises with increasing MgCl_2 and falls with rising $[\text{MgCl}_2]$ of the next. B. C. P. V.

Reaction between bitumen emulsions and fillers. E. S. Medvedkov and A. F. Sakhina. *Bumuschnaya Prom.* 18, No. 7, 38-40 (1970). Insufficiently stable bitumen emulsions are destroyed by powdery and fibrous fillers such as asbestos, linters, sulfite cellulose, kieselguhr, kaolin and wood flour. The stability of the emulsions may be increased by increasing the concn. of the emulsifier, decreasing the diam. of the emulsified bitumen droplets or by preliminary treatment of the filler with the emulsifier. The destruction of the emulsions in the presence of an electrolyte is analogous to the coagulation of colloidal sols under the action of electrolytes. In this case the filler apparently plays a secondary role. The limits of coagulation for $\text{Al}_2(\text{SO}_4)_3$ and CaCl_2 in the presence of linters in the emulsion are 0.003-0.01 and 0.001-0.003 g. mol. l.
B. Z. Kamich

Hydroxylfuchson dyes. IX. Structure and color of hydroxymethoxyfuchson. I. S. Ioffe and A. F. Sukhina. Zhur. Obshchel Khim. (J. Gen. Chem.) 19, 1107 (1939); cf. C.A. 33, 8683d.—Absorption curves are given for fuchson, 3-methoxyfuchson, benzaurine, mono- and di-3-methoxybenzaurines, aurine, and its derivs. in unionized state give similar curves in the visible region, but HO and MeO groups cause a small bathochromic shift. Hydroxylfuchsones in mineral acids give curves which are identical regardless of the nature of the acid. Benzaurines are more intensely colored in acid or alk. solns. than the aurines. MeO groups cause a small bathochromic shift in aurines and benzaurines (in acid or alk. solns.). The most satisfactory alk. soln. was 1% borax, as strong alkalies yield colorless carbinol base anions.

G. M. Kosolapoff

25

Sukhina, A.F.

Quinonoid series. II. Chloroquinoxquinones. I. S. L. Joffe and A. F. Sukhina. *Zhur. Obshchey Khim.* 2A, 207-9 (1953); *J. Org. Chem.* 18, 729 (1953). Methylation of chloro-*p*-benzoquinone with MeOH-ZnCl₂ leads not only to introduction of MeO group, but also to displacement of the Cl by a 2nd MeO group. To 6 g. vanillin in 40 ml. 4% NaOH was rapidly added 30 ml. 5% H₂O₂, and the dark brown soln. treated after 1 hr. with 8 ml. 20% H₂SO₄ (5 ml.), chilled, then treated at -3° with 40 g. NaCrO₇ in 75 ml. 20% H₂O₂ over 2 hrs., followed by 2 hrs. at 0°, giving 3.9 g. (71%) methoxy-*p*-benzoquinone, m.p. 111° (from EtOH). Direct chlorination of vanillin in CHCl₃ gave 2,5-dichloro-(MeO)C₆H₃CHO, m.p. 163°, which (9 g.) in 30 ml. 4% NaOH treated as described above with 30 ml. 5% H₂O₂ (5 ml.) and with 20% H₂SO₄, and chilled gave a ppt. of 6-chloro-2-methoxy-*p*-benzoquinone, m.p. 140°; the latter can be directly oxidized with NaCrO₇ at -5° as described, yielding 77% 6-chloro-2-methoxy-*p*-benzoquinone, orange, m.p. 158° (from EtOH). Similar treatment of 2,4,5-tri-CH₃O-*p*-benzoquinone (MeOC₆H₃Cl)₂ gave 60% 3,4,5-tri-CH₃O-*p*-benzoquinone (EtOH), yellow, m.p. 172-3° (from EtOH), insol. in AcOH and *CHCl*₃ but soluble in *CHCl*₃ more easily than the 6-Cl analog. The yield of 2,5-dichloro-*p*-benzoquinone by the Bueler method [Ber. 34, 233 (1901)] is increased beyond 33% by addition of oxidizing agents to the reaction mixt. and thus reducing the consumption of the starting material in oxidation-reduction reactions listed, and the yields were even lower than without such addition. FeCl₃, PbO₂. III. Chlorination of methoxyquinone. *Ibid.* 299-303.—Passage of HCl into methoxy-*p*-benzoquinone (I) in *CHCl*₃ gave a blue-violet ppt., free of Cl, m.p. 238-40° (from PhNO₂), also formed on addn. of mineral acids to I in AcOH. The product has been described earlier (Bretman, *J. Am. Chem. Soc.* 59, 1737). Thus I reacts in the presence of mineral acids. Passage of Cl₂ into I in *CHCl*₃ yielded a blue-violet ppt., m.p. 238-40° (from PhNO₂).

(S. F. S.)

decomp., 159°, losing HCl and yielding an orange intermediate, *3-chloro-2-methoxy- β -benzoquinone. Thus, introduction of a MeO group reduces the stability of quinone dichlorides. *β*-*MeO-phenylbenzene dichloride*, m. 148°, without decompr., and only at 170-80° does it lose HCl, yielding an unstable monochloroquinone (cf. Dimoneth, et al., C.A. 20, 1994). Chlorination of tertiary-*β*-benzoquinone must be done with pure Cl, for even traces of HCl lead to dimerization mentioned above. The heating of the *α*-methoxyquinone dichloride is best done by spreading the substance in a thin layer in a dish and heating to 125° in a thermostat. Although its decompr. can lead to 2 isomeric chloromethoxy-*β*-benzoquinones, the product actually obtained is the pure chloro-2-methoxy isomer, m. 173°. The acid reaches 70%. The methoxyquinone dichloride is also unstable on heating in various solvents. Thus in hot aq. EtOH it loses HCl and yields up to 60% *6-chloro-2-methoxy- β -benzoquinone*, m. 159°. Addn. of the dichloride to hot AcOH gave *5-chloro-2-methoxybenzoquinone*, m. 172.3°, also formed in hot dry Me_2CO . But in *an* AcOH and *an* Me_2CO the 6-Cl analog is formed. In hot H₂O the dichloride also yields the 6-Cl deriv. Heating the dichloride in aromatic hydrocarbons under dry conditions gives different results; the substance is not decompr. 1. in boiling zylene for over 1 hr., while hot C₆H₆ can be used as recryst. solvent; the dichloride thus purified m. 120° (decomp.). A trace of H₂O immediately yields 6-chloro-2-methoxy-*β*-benzoquinone. G. M. K.*

IOFFE, I. S.; SUKHINA, A. F.

Quinone

Investigation of quinones. Part 3. Chlorination of methoxyquinone. Zhur. ob. khim. 23, No. 2, 1953.

Monthly List of Russian Accessions, Library of Congress, June 1953. Uncl.


Chen Abi

118 35 Jan 11

118 - 2

Organic Chem

✓ Quinone series. IV. Transformation of methoxy-
quinone under the influence of acids. J. S. Joffe and A. F.
Sukhina. *Zhur. Obrshch. Khim.* 23, 1370-6 (1953); cf.
ibid., 292; Erdman, *C.A.* 48, 1307. In contrast with
other quinones, methoxyquinone (I), under the action
of mineral acids, forms a condensation product with forma-
tion of a biphenyl link in a position para to the MeO group.
Thus 10 g. I in 100 ml. warm ArOH, poured into 2 l. 1%
HCl, gradually yields a blue ppt., which after 48 hrs.
amounts to 95% II, m. 230° (crude), m. 238° (from pyri-
dine), which is generally but sparingly sol. in org. solvents.



Reduction of 3 g. II with 3 g. Zn dust in refluxing AcOH gave, upon filtration, diln., and treatment with dil. NaHSO₃, a 60% yield of [6,2,4-(HO)₂MeOC₆H₃]₂, decomp. 210° (from dil. EtOH); *tetra-Ac derivative* from Ac₂O-pyridine, m. 188-7° (from EtOH). II (3 g.) agitated with 3 g. chromic acid in 300 ml. H₂O gave III, m. 212-14° (from AcOH). I (1 g.) in 10 ml. AcOH treated with 20 ml. concd. HCl gave after 48 hrs. 75% 5,5'-dihydroxy-4,4'-dimethoxy-3-chlorodiphenyl oxide, m. 230-1° (from AcOH), colorless, the *diacetate* (Ac₂O-pyridine), m. 220-1° (from AcOH); also obtained in 95% yield from II in warm AcOH with concd. HCl, the blue color of II being discharged at 65-70°. III (5 g.) in 25 ml. AcOH refluxed with 25 ml. concd. HCl gave 85% 5,5'-dihydroxy-4,4'-dimethoxy-3,3'-dichlorodiphenyl oxide, m. 235-6° (from AcOH); *diacetate*, m. 252-3° (from AcOH).

G. M. Kosolapoff

(2)
child

APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9"

"APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9

APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9"

SUKHINA, A. F.

USSR/Chemistry

Card 1/1

Authors : Ioffe, I. S. ; and Sukhina, A. F.
Title : Investigation of quinones. Part 9.- Reaction of methoxyquinones with amines.
Periodical : Zhur. Ob. Khim. 24, Ed. 4, 705 - 709, April 1954
Abstract : The reaction of methoxyquinones with amines shows two trends:
1) addition of the amino radical to the non-substituted carbon atom of the quinoid nucleus and 2) displacement of the methoxyl group by the amino group. The amino radical subjected to the effect of the methoxyl group rapidly attaches itself to the non-substituted carbon atom provided the latter is in para-position relative to the amino group. Displacement of methoxyl group by still another amino radical at an aniline surplus is already much slower. Six references; 3 USSR since 1946; 1 English 1946; 2 German since 1891. Chemical formulas.
Institution :,
Submitted : July 28, 1953

"APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9

SUKHINA, A.F.

5-Chloro-8-hydroxyquinoline. Zhur.ob.khim. 32 no.4:1356-1357
Ap '62. (MIRA 15:4)
(Quinolinol)

APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9"

IOFFE, I.S.; SUKHINA, A.F.; ZHUKOVA, Ye.N.

Rhodamine dyes and related compounds. Part 6: Chloride and
amides of sulforhodamine B. Zhur.ob.khim. 32 no.5:1489-1492
My '62. (Rhodamine)

S/079/63/033/001/022/023
D204/D307

AUTHOR: Sukhina, A. F.

TITLE: The sulfonic acid of benzylacridine

PERIODICAL: Zhurnal obshchey khimii, v. 33, no. 1, 1963, 317

TEXT: Benzylacridine was heated with 96% H_2SO_4 at $100^{\circ}C$, and was then neutralized with aq. NaOH; the precipitated Na sulfonate was dissolved in hot water and the free sulfonic acid was obtained by precipitation on acidifying the water with H_2SO_4 . After recrystallization from water, the acid appeared in the form of fine yellow plates, sparingly soluble in alcohol and acetone. The aqueous solutions exhibited an intense blue-green fluorescence. The Na salt was obtained from concentrated aqueous solutions in the form of colorless needles. Both compounds are new. [Abstracter's note:
Essentially complete translation.]

SUBMITTED: July 6, 1962

Card 1/1

IOFFE, I.S.; SUKHINA, A.F.; ZHUKOVA, Ye.N.

Rhodamine dyes and related compounds, Part 8: Amides of sulfo-
rhodamine B containing N- β -hydroxy and β -chloroethyl groups.
Zhur.ob.khim. 33 no.12:3943-3946 D '63. (MIRA 17:3)

L 29307-66 FWT(m) IJP(c) GD
ACC NR: AT6012261

SOURCE CODE: UR/0000/65/000/000/0001/0013

AUTHCRS: Budker, G. I.; Dimov, G. I.; Popov, A. G.; Sviridov, Yu.K.;
Sukhina, B. N.; Timoshin, I. Ya.

53

B+1

ORG: Institute of Nuclear Physics, Siberian Department AN SSSR
(Institut yadernoy fiziki Sibirskogo otdeleniya AN SSSR)

TITLE: Experimental investigation of charge-exchange injection of
protons in annular accelerators and storage rings
19

SOURCE: AN SSSR. Sibirskoye otdeleniye. Institut yadernoy fiziki.
Doklady, 1965. Eksperimental'noye issledovaniye perezaryadnoy
inzheksii protonov v kol'tsevyyee uskoriteli i nakopiteli, 1-13

TOPIC TAGS: charge exchange, proton accelerator, energy scattering,
circular accelerator

ABSTRACT: The authors describe experiments on the accumulation of protons in an annular track by means of a charge exchange (Fig. 1). A beam of atoms or negative ions of hydrogen is introduced on a proton orbit in a magnetic field at the point where it crosses a hydrogen jet. The particles lose electrons in the jet and are accumulated on the orbit in the form of protons. The protons passing many times through the jets lose energy and are scattered. In a constant magnetic field the time of

Card 1/3

L 29307-66

ACC NR: AT6012261




Fig. 1. Diagram of experimental setup. 1 - Source of negative hydrogen ions, 2 - accelerator, 3 - input gas target, 4 - Jet of hydrogen on orbit, 5 - storage ring

Card 2/3

L 29307-66

ACC NR: AT6012261

accumulation is limited by the loss of the circulating protons to the inner wall of the storage ring. If the average energy loss is compensated for, the storage time is limited by elastic scattering and by the energy scatter of the protons. The experimental setup was described elsewhere (Mezhdunarodnaya konferentsiya po uskoritelyam Dubna, 1963, [International Conference on Accelerators], Moscow, 993 -- 996, 1964). Methods of measuring the proton current and the proton lifetime in the storage ring are briefly described. Various parts of the experimental setup are described in detail. The ion source was a modified electrostatic generator. Up to 10^{12} protons could be accumulated in the betatron loop (current ~ 1 ampere). The injection efficiency was close to 100%. Hydrogen and carbon dioxide were used for the input targets, with optimal thickness 2.5×10^{16} and 3×10^{15} mol/cm². An accelerating voltage of 200 v was applied in pulses of 500 μ sec duration, so that accumulation for 2500 revolutions was possible. The loop current increased approximately linearly to 300 ka. The various sources of losses are briefly analyzed. Orig. art. has: 8 figures and 7 formulas.

SUB CODE: 20/ ORIG REF: 001/ OTH REF: 001

Card 3/3 BK

L 25774-66 EWT(m) IJP(c)

ACC NR: AP6016378

SOURCE CODE: UR/0089/65/019/006/0507/0510

AUTHOR: Budkar, G. I.; Dimov, G. I.; Popov, A. G.; Sviridov, Yu. K.; Sukhina, B. N.; Timoshin, I. Ya.

ORG: none

TITLE: Experiments with charge exchange injection of protons in a storage ring

SOURCE: Atomnaya energiya, v. 19, no. 6, 1965, 507-510.

TOPIC TAGS: Van de Graaff accelerator, proton, hydrogen ion

ABSTRACT: Negative hydrogen ions were extracted from a high frequency source and were accelerated in a Van de Graaff machine to $12 \mu\text{amp}$. This beam then struck a neutralizing gas target of hydrogen or carbon dioxide having an optimum thickness of 2.5×10^{16} or 3×10^{15} molecules/cm² respectively. The resulting beam of neutral hydrogen atoms then struck a jet of hydrogen having a thickness of $\sim 10^{17}$ atoms/cm². The hydrogen jet was directed along a radius from the center of a storage ring with an aperture of 8 \times 4 cm and an orbital radius of 42 cm. The particle losses did not exceed a few percent with injections up to 150 revolutions. The orbital current increased linearly for the first 100 revolutions and remained constant for ~ 150 revolutions. During this period the orbital radius of the beam decreased and then struck the internal hydrogen stream. Thus the injection efficiency was close to 100%. These preliminary results indicate that it is possible to accumulate a proton current that is limited only by the space charge. Orig. art. has: 5 figures. *NA*

SUB CODE: 20 / SUBM DATE: none

Card 1/1 10

34
B

Z

SUKHINA, I.A.

Making axonometric drawings of assemblies. Trudy KIPP no.16:
127-132 '57.
(MIRA 12:7)

I. Krasnodarskiy institut pishchevoy promyshlennosti, Mekhaniko-
cheskiy fakul'tet, kafedra nachertatel'noy geometrii i grafiki.
(Axonometric projection)

SUKHINA, I.A.

Frontal oblique isometry. Trudy KIPP no.16:133-135 '57.
(MIRA 12:7)

1. Krasnodarskiy institut pishchevoy promyshlennosti., Mekhaniko-
cheskiy fakul'tet, kafedra nachertatel'noy geometrii i grafiki.
(Axonometric projection)

SUKHINA, V.Ya., inzh.

Determining the gear ratio and the efficiency of planetary
transmissions. Vest.mash. 42 no.4:37-43 Ap '62. (MIRA 15:4)
(Gearing)

SUKHINENKO, G. A.

86-9-5/36

AUTHOR: Sukhinenko, G.A., Lt.Col.

TITLE: Air Blockade of an Airfield by Bombers at Night (Blokiro-vaniye aerodroma bombardirovshchikami noch'yu)

PERIODICAL: Vestnik Vozdushnogo Flota, 1957, Nr 9, pp. 14-17 (USSR)

ABSTRACT: In this article the author describes the organization and the procedure of a group exercise by a bomber subunit on the ground in order to study the tactics of bombers in air blockade of enemy airfield at night, to study of the execution of flak evasive maneuvers, and to teach the flying personnel in the proper estimation of the ground and air situation and in making the necessary decisions. One map.

AVAILABLE: Library of Congress

Card 1/1

"APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9

SUKHINICH,A., inzhener

On a practical way of reinforcing embankments. Rech. transp. 14
no, 4:11-12 Ap '55. (MIRA 8:6)
(Embankments)

APPROVED FOR RELEASE: 07/13/2001

CIA-RDP86-00513R001653810017-9"

SUKHININ, A. A.

USSR/ Biolog. - Ornithology

Card 1/1 Pub. 86 - 30/37

Authors : Sukhinin, A. A.

Title : The black stork in Turkmen

Periodical : Priroda 44/4, 117 - 118, Apr 1955

Abstract : An account is given of observations made of the habits of the black stork, covering migrations in February and September, nest buildings on crags and rearing of young. The nesting was observed in mountainous regions of Turkmen near waters containing a food supply. Three Soviet references (1940 - 1952).

Institution :

Submitted :

SUKHININ, A.N.

Black stork in Turkmenistan. Priroda 44 no.4:117-118 Ap '55.
(MIRA 8:4)

1. Bakhyzskiy gosudarstvennyy zapovednik, Turkmenskaya SSR.
(Turkmenistan—Storks)

SUKHININ, A.N.

Data on the distribution of certain birds in Turkmenia. Zool.
zhur.35 no.5:779-780 My '56. (MIRA 9:9)

1.Badkhyzskly gosudarstvennyy zapovednik.
(Turkmenistan--Birds)

RUSTAMOV, A.K.; SUKHININ, A.N.

New information on birds of southern Turkmenia. Izv.AN Turk.SSR
no.4:70-76 '57. (MIRA 10:10)

1. Turkmenskiy sel'skokhozyaystvennyy institut im. M.I.Kalinina,
Badkhyzskiy gosudarstvennyy zapovednik.
(Turkmenistan--Birds)

SUKHININ, A.N.

Materials on the ecology of the Turkestan harrier eagle *Circaetus
farox heptneri* Dem. in Badghis. Izv.AN Turk. SSR no.5:132-135 '57.
(MIRA 10:10)

1.Balkhyzskiy gosudarstvennyy zapovednik.
(Badghis--Hawks)

SUKHININ, A.N.

Materials on the reproduction and nourishment of the raven in
Badkhyz, Izv. AN Turk. SSR no.2:88-92 '58. (MIRA 11:4)

1. Badkhyzskiy gosudarstvennyy zapovednik.
(Turkmenistan--Ravens)